HPRT
Your Future, Printed

HT400

Standard thermal transfer desktop barcode printer with 300-meter ribbon supported



Characteristic

- 152.4 mm/s (6") per second printing speed
- Mechanism structure design, easy for maintenance
- 1.1 GHz 32-bit RISC processor with 64 MB SDRAM 128 MB Flash memory
- USB, Ethernet interface as standard, optional Wi-Fi or Bluetooth
- Free Seagull Windows driver and Bartender, and HPRT drivers and label design software
- ZPL II, DPL, TSPL, EPL emulation supported
- Various accessories include peeler, cutter, and external paper stand

The Details Show





Specification

Model	HT400	
Printing	Printing Method Resolution Max. Printing Speed Max. Printing Width Max. Printing Length	Thermal Transfer 203 dpi/300 dpi 6 ips (203 dpi), 5 ips (300 dpi) 108 mm (203 dpi)/106 mm (300 dpi) 2286 mm
CPU		32-bit RISC CPU
Memory	RAM Flash	64 MB 128 MB
Detection	Sensor	Out-of-paper detection, gap detection, ribbon detection, black mark detection, cover-opening detection
Media	Type Width Height Thickness O.D. I.D.	Black mark label, punched hole label, folding or rolling die cutting label 20 mm – 118 mm 8 mm – 250 mm 60 µm – 200 µm Max. 5 inches (127mm) 1 inch（25.4 mm），1.5 inches(38 mm)
Ribbon	Type Width Length Core Diameter	Wax, Wax/Resin, Resin 40 mm –110 mm Max. 984feet (300 m) 0.5/1 inch
Programming Language		ZPL II, TSPL, DPL, EPL
Software	Label Design Software Driver	HPRT BarTender Ultralite Windows 7,8,10, Server 2012/2016/2018, Seagull Driver
Resident Fonts	Bitmap Font TTF Fonts	6, 8, 12, 16, 32, OCR A & B. 90°, 180°, 270° rotatable and 10 magnification. CG Triumvirate™times expandable in horizontal and vertical directions, simplified Chinese.
Codepage		DOS437,720,737,755,775,850,852,855,856,857,858,860,862,863,864, 865,866, Windows 1250,1251,1252,1253,1254, 1255,1256,1257,1258, ISO8859-1,-2,-3,-4,-5,-6,-8,-9,-15
Barcode	1D 2D	Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 PDF417, Maxicode, DataMatrix, QR Code, Aztec
Interface	Standard Optional	USB, Ethernet Bluetooth 5.0/BLE,WiFi
User Interface		Two-color status light: standby, abnormal indication Feeding button: Feed, :Calibration Button:Calibrate
Power Supply		Power Switch Input: AC 100-240 V, 50/60 Hz Output: DC 24 V / 2 A
Environment	Operation Storage	41°F(5°C) to 104°F(40°C) , humidity 30% to 85% ,non-condensing -4°F(-20°C) to 122°F(50°C), humidity 10% to 90% ,non-condensing
Physical Characteristic	Dimension(L*H*W) Weight	282 mm×205 mm×168 mm (L×W×H) 2.32kg, excluding media
Options & Accessory		Peeler module, Guillotine cutter, external label roll holder,Rotary cutter
Agency Approval		CCC,CE,FCC,CB

HPRT
Your Future, Printed

Xiamen Hanin Co.,Ltd.

Address: 1-5F, NO.8,Gaoqi South 12th Road,Xiamen,China
Telephone: +86-(0)592-5885993 (English)
E-mail: overseas@hprt.com
Website: www.hprt.com

Brochure Version: 202602

HPRT Official Website